CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION OFFICE OF THE STATE FIRE MARSHAL

FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM

LISTING SERVICE

LISTING No. 3225-0368:114 Page 1 of 1

CATEGORY: Fire Dampers

LISTEE: Pottorff, *2824 N. Sylvania Ave., Fort Worth, TX 76111

Contact: Michael Beaver (817) 831-7038

DESIGN: Models VFD-15R and VFD-35R round fire dampers. Unit constructed of No. 22 Ga.

galvanized steel frame, blades and blade hinge with a 165° F or 212° F fusible link.

Refer to listee's data sheet for detailed product description and operational

considerations.

RATING: VFD-15R: 1-1/2 Hr.

> VFD-35R: 3 Hr.

Single Section Size: minimum 6" and maximum 20" in diameter

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances

and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee's name, model number, fire rating and UL label.

APPROVAL: Listed as fire rated dampers for use in heating, ventilating and air conditioning duct

systems passing through fire resistive walls and partitions. Model VFD-15R is intended for

vertical and horizontal mount. Model VFD-35R is intended for vertical mount only.

NOTE: Leakage rating not evaluated. Refer to CSFM Listing Category 3230 for leakage rated

dampers.

*Rev 06-15-99



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other suitable information sources.

MAY 15, 2002 Date Issued: Listing Expires June 30, 2003

Authorized By: **DIANE K. AREND**, Senior Deputy

Program Manager